





IGNITE THE POWER OF NATURE

Monocrystalline Module 250Watt

Model (SL250TU-48MBK) Specifications



Electrical Data

Maximum Power(W)	250
Optimum Power Voltage(Vmp)	51.80
Optimum Operating Current(Imp)	4.83
Open Circuit Voltage(Voc)	61.10
Short Circuit Current(Isc)	5.16
Cell Efficiency (%)	17.66
Module Efficiency (%)	14.80
Tolerance Wattage(%)	0~+3%
NOCT	47°C +/-2°C

Temperature Coefficients

Temperature Coefficients of Isc(%)°C	+0.04
Temperature Coefficients of Voc(%)°C	-0.35
Temperature Coefficients of Pm(%)°C	-0.45
Temperature Coefficients of Im(%)°C	+0.04
Temperature Coefficients of Vm(%)°C	-0.35

Components & Mechanical Data

Solar Cell	125*125 Mono
Number of Cell(pcs)	8*12
Size of Module(mm)	1600*1056*40
Front Glass Thickness(mm)	3.2
Surface Maximum Load Capacity	2400-5400Pa
Allowable Hail Load	23m/s ,7.53g
Weight Per Piece(KG)	19.5
Junction Box Type	Pass the TUV Certificate
Bypass Diode Rating(A)	12
Cable & Connector Type	Pass the TUV Certificate
Frame(Material Corners,etc.)	40#
Backing (Brand Type)	TPT
Temperature Range	-40°C to +85°C
FF (%)	70-76%
Standard Test Conditions	AM1.5 1000W/m ² 25°C

Benefits



Modules sorted by current,
optimizing system power
generation



High Efficiency



Stable Power



Low Carbon Emission



Excellent Weather
Resistance




IGNITE THE POWER OF NATURE


QXPV

Monocrystalline Module 250Watt


IV-Curves



IV-CURVES of PV module
SL250TU-48MBK



Engineering Drawings



Warranty & Certifications

Warranty	25 years limited power warranty
	10 years limited product warranty
Certifications	IEC 61215, IEC 61730

Packing

Packing	Wooden Box
1*20'	14Pallets/330pcs
1*40'HQ	28Pallets/784pcs

Applications

- ☐ On-grid residential roof-tops
- ☐ On-grid commercial/industrial roof-tops
- ☐ Solar power stations
- ☐ Other on-grid applications

Project Picture



☐ Manufacturing facility certified to **ISO 9001 / ISO 14001 / OHSAS 18001** quality management system standards.

©2013 Ningbo Qixin Solar Electrical Appliance Co., Ltd. All rights reserved.
Specifications included in this datasheet are subject to change without notice.

Ningbo Qixin Solar Electrical Appliance Co., Ltd
ADD: No. 37 Jingang Road, Binhai Industrial Park,
Xiangshan County, Ningbo, 315700, China
TEL: 0086 (0)574 25758821
FAX: 0086 (0)574 25758820
E-mail: info@nbqxsolar.com

